PRODUCT FEATURES & APPLICATION



Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

HI-BUILD WELD THRU PRIMER "COLD GALVANIZING SPRAY"

Stock SZC Part # 24090

Colour: Grey

Description:

Dominion Sure Seal's Hi-Build Zinc Rich Weld-Thru Primer / Coating is a very fast drying, anticorrosive coating that is normally applied to metal surfaces prior to welding. This one stage aerosol is also referred to as "Cold Galvanizing Compound". It will reduce mig weld "splatter" and can be applied to metal surfaces after welding. It will give corrosion protection before and after welding.

Features:

- Fast Dry (10 15 minutes)
- Excellent Corrosion Protection
- Easily applied before welding
- Reduces "mig" weld splatter
- Add superior corrosion to all bare metal.
- Ideal for areas that may be welded
- Can also be applied to areas after welding for added anti-corrosion protection

Full Cure 10-30 Min

Application Instructions:

- 1) Surfaces to be coated must be free of all grease, oil and other contaminants.
- Use Dominion Sure Seal "SURE-SOLV"
 General-Purpose Universal Solvent stock BSS
 qt & SUS-24oz aerosol.
- 3) Allow cleaner to flash-off completely before application.
- 4) This is a High Solids product and must be thoroughly shaken prior to application.
- 5) Be sure to shake can well until the "ball" inside breaks free and begins agitating the material.
- 6) From an 8-10 inches (20-25cm) distance from surface, apply material until complete coverage is achieved. 2nd coats may be applied after 10 minutes.

Be sure to invert can and spray until nozzle is clear. This will prevent blockage.

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.

Call 1-800-265-0790 or visit us on the web www.dominionsureseal.com