PRODUCT FEATURES & APPLICATION

Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

ONE STEP Automotive Self Etch Primer

Stock SEP Part 24008

340 g/16 0z. Aerosol

DECRIPTION: One Step is unique and convenient to use 'etch type' primer that provides excellent adhesion for additional top coats, primers, and sealers to metals. This product is compatible with all Automotive primer surfacers for spot repair and refinishing.

Apply to steel, aluminum, and most metals

FEATURES

- Fast drying.
- Excellent sanding, if necessary.
- Strong adhesion to metals, and other substrates.
- Great adhesion to stainless steal
- Great adhesion to most galvanized metals.
 Galvanized depends on the adhesion of the galvanized coating to the substrate.
- Superior adhesion of primer surfacers and other topcoats to product.
- Great filling characteristics.

APPLICATION:

- 1. Surface should be free of rust and scale.
- 2. Clean area to be primed with Sure Solve (BSS) or a good quality wax and grease remover removing all wax, grease, silicones, and contaminates.
- 3. Feather edge (sand) original finish. Do not use over fresh paint.
- 4. Vigorously shake can for 1 minute agitating material.
- 5. Apply 2-3 even coats holding can 10 15 inches from surface.
- 6. Material can be topcoated and/or sanded within 2 hours. This is important for maximum adhesion of primer to substrate.