

Product Description

Dupli-Color® Filler Primer features a high build automotive formulation capable of filling deep scratches and minor surface imperfections. A fast-drying, sandable finish allows for easy feather edging while providing a smooth and rust resistant surface that promotes top coat uniformity.

Product Characteristics

Colors: Gray & Red Oxide.

Properties

Product Weight: 6.89 lb/gal

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Filler Primer provides an optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax Remover
Prime	FPxxx	Filler Primer

Refer to the product label for more specific instructions!

Uses

Deep Scratches & Minor Surface Imperfections.

Surfaces:

Metal, Fiberglass & Wood.

Application

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover to clean surface. Sand surface with 320-grit sandpaper, wet or dry. Wash with mild soap and water. Rinse well, and dry well with a clean cloth.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60°-92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs and sags, apply in light coats. Allow surface to dry 10 minutes between coats, and 30 minutes before sanding or applying finish coat of paint. If needed, sanding can be done wet or dry after 30 minutes with 600 grit sandpaper.

(Note: Product is not recommended for use on damaged areas more than 1/16 of an inch deep). Can be handled in one hour. Covers approximately 12-14 square feet. When primer application is complete, refinish primed area with the appropriate Dupli-Color aerosol paint.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.

Packaging

Fill Weight: 11 oz

Per Case: 6 cans

Case Weight: 6 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans